

CAMERA

PT-3160-HD30PTZ

KEY FEATURES

- AI VIDEO ANALYTICS**
 8 Intelligent OCR modes powered by AI engine which filters objects to focus on human and vehicle detection
- 30X OPTICAL ZOOM**
 Zoom into distant subjects while still maintaining clarity delivering high quality video the entire zoom range
- PEOPLE COUNTING**
 Real time AI based people counting, including statistic reports for operational efficiency
- UP TO 90FPS**
 Cameras catch images with no latency during high speed movement



LEARN MORE ABOUT THIS PRODUCT

Ultra Low Light

Able to deliver high detailed color images even in 0.005LUX low light environments without any supplemental lighting.

Smart IR II

Self Adjusting Infrared high beam and low beam functionality suitable for all lighting conditions. Up to 200m.

HLC

High Light compensation. Improving image visibility under strong light sources.

IP66-Rated Resistance

Camera is built to withstand all weather conditions.

Local Storage Backup

Up to 1 Terabyte local storage for video backup.

120dB Super WDR

The cameras built in Super WDR produces quality images across all ranges of light level.

IK10-Vandal Proof

Camera withstands the highest rated impact testing using international standards.

CREATE A SMART CITY

POWERED BY PACKETALK

-  **Customize a mobile surveillance trailer**



Diesel-Powered Surveillance Trailer PT-RD6000

-  **Add a LPR**

Our License Plate Recognition is an AI-based license plate detection, recognition and search solution with an accuracy as high as 98%.

-  **Deploy iSMART**

The interactive Situational Monitoring Analysis Response Tool (iSMART) is a proven real-time situational awareness, problem solving, and resource management

QUESTIONS? CONTACT US AT

201 355 3323 OR sales@packetalk.net



For PDF of PTZ-3160-HD30PTZ

SPECIFICATIONS

| CAMERA | |
|---------------------------|--|
| Image Sensor | 1/2.8" Progressive Scan CMOS |
| Min. Illumination | Color: 0.005Lux@F1.5 B/W: 0Lux with IR on |
| WDR | 120dB Super WDR |
| Shutter Time | 1/100000s~1s |
| Digital Zoom | 16X |
| Day/Night Mode | Day/Night/Auto/Customize/Schedule |
| S/N | >55dB |
| LENS | |
| Lens | 4.7~141mm, 30x Optical Zoom |
| Field of View | H63°~H3°/D70°~D3°/V37°~V1° |
| Focus Control | Auto/Semi-Auto/Manual |
| Iris Control | Auto |
| PTZ | |
| Pan Range/ Pan Speed | 360°endless Pan Manual Speed: 0.1°~250°/s Pan Preset Speed: 250°/s |
| Tilt Range/ Tilt Speed | -5°~90°(Auto Flip) Tilt Manual Speed: 0.1°~160°/s Tilt Preset Speed: 160°/s |
| Preset Quantity | 300 |
| Other Function | Auto Scan, Auto Home, Preset Freezing, 3D Positioning, PTZ Limits, Initial Position |
| IR | |
| IR Distance | Up to 200m |
| IR Angle | Auto/Manual |
| VIDEO | |
| Max. Image Resolution | 1920x1080 |
| Video Compression | H.265+/H.265(HEVC)/H.264+/H.264/MJPEG |
| Image Setting | Brightness/Contrast/Saturation/Sharpness |
| INTERFACE | |
| Ethernet | 1*RJ45 10M/100M Ethernet Port |
| Audio I/O | 1/1 |
| Alarm I/O | 4/2 |
| NETWORK | |
| Network Storage | NAS (Support NFS, SMB/CIFS), ANR |
| Protocol | IPv4/IPv6, ARP, TCP, UDP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL |

| INTELLIGENT ANALYTICS | |
|---------------------------|---|
| Video Analysis | Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed |
| People Counting & Report | Count the number of people entering or exiting, up to 4 detection areas for regional people counting |
| SYSTEM | |
| Storage | Support microSD/SDHC/SDXC Card Local Storage, up to 1TB |
| Advanced Function | BLC, HLC, 2D DNR, 3D DNR, AWB, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur, Watermark |
| Event Trigger | Motion Detection, Network Disconnection, External Input, Audio Alarm, etc. |
| Event Action | FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, PTZ Motion, HTTP Notification, etc. |
| System Compatibility | ONVIF Profile G & Q & S & T, API |
| GENERAL | |
| Working Condition | Temperature: -40°C~60°C/ Humidity: 0~90%(Non-condensing) |
| Power Supply | PoE (802.3at) / AC 24V/3A±10% |
| Power Consumption | 12W |
| Weather Proof/ Housing | Up to IP66-rated for Weather-resistant Performance / Vandal-proof IK10-rated Metal Housing (Optional) |
| Surge Protection | 6KV |
| Dimensions/ Weight | Φ205mmX308mm/4Kg |



For more Packetalk Cameras

GET IN TOUCH

CONTACT US

T (201) 355-3323

F (201) 603-6405

E sales@packetalk.net

PACKETALK.NET

© 2023, Packetalk. The Packetalk logo is a registered trademark of Packetalk. All other company names and products are trademarks or registered trademarks of their respective companies. All information provided is subject to change without notice.