

TRAILER

PT-RD3000

PORTABLE, OUTDOOR HD VIDEO SURVEILLANCE SYSTEM

KEY FEATURES

- SOLAR POWERED
- HD PTZ IP CAMERA
- LARGE BATTERY BACKUP
- OPERATES IN EXTREME ENVIRONMENTS
- REAL-TIME MONITORING
- REMOTELY MONITORED AND CONTROLLED
- 24/7 UNATTENDED OPERATION
- LIGHTWEIGHT FOR EASY DEPLOYMENT



(Typical Configuration)*

LEARN MORE ABOUT THIS PRODUCT

Self-Contained

Temporary surveillance systems that provide high definition live video of the deployment location.

Remote Monitoring

Monitor critical areas, incident areas, and other problem locations whenever and wherever necessary in a compact, mobile, self-powered unit.

Pan-Tilt-Zoom (PTZ) and Bubble Cameras

Configuration supports up to five cameras including:

- 30x-36x Optical Zoom
- ALPR and OCR based Video Analytics
- Fixed Dome camera with up to 5x Zoom
- 360° Degrees of detail
- Up to 4k @ 90FPS video output

* Standard Trailer configuration comes with two AI PTZ cameras and one AI fixed dome camera pointed at the trailer for anti-vandalism purposes. Customization is available upon request.

Management Software

Camera can be controlled automatically and precisely from anywhere using management software included with the system.

"Always On" Network

The system is shipped, preconfigured, and ready for deployment on leading broadband cellular networks.

On Board Self Healing

Autonomous operational continuity dashboard allows users to actively monitor and manage trailer vitals for all assets in a centralized location from desktop, phone, or tablet.

CREATE A SMART CITY

POWERED BY PACKETALK

✓ Add a ALPR asset

Packetalk's ALPR cameras have embedded license plate recognition, AI video analytics and up to 90FPS.



PTZ-3160-HD36ALPR

✓ Add PTVAS

Packetalk Video Analytics System provides a multi-faceted situational awareness platform for all your surveillance needs.

✓ Deploy INAAP

Packetalk Interoperable National ALPR & Analysis Platform. Creates Interoperability across county and state lines for Plate recognition and vehicle exception reports. Equipped with API and third Party integration.

QUESTIONS? CONTACT US AT
201 355 3323 OR sales@packetalk.net

PACKETALK.NET

PT-RD3000

SOLAR-POWERED WITH
LARGE BATTERY BACKUP



CAMERA BOOM

Full camera customization available with different PTZ functionality including ALPR, video analytics, people counting and thermal imagery.



ON BOARD SELF HEALING

Built in monitoring system collects data and information for display in our autonomous operational continuity vitals application.



BREAKERS & BATTERIES

Rapid deploy breakers protect internal components turning the trailer into an easy "Fire and Forget" asset.

SPECIFICATIONS

TOWER DIMENSIONS		PTZ CAMERAS (CON'T)	
Width (Travel/Deployed)	79"/151"	Compression	MJPEG, H264, H265
Length	120"	Minimum Illumination	Color: 0.05 LUX@F1.6 B/W: 0.0 LUX@F1.6
Height (Travel/Deployed)	111"/300"	Video Analytics	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed
Weight (Dry/Operating)	Dry 1600 lbs/ Operational 2200 lbs	Traffic Detection	License Plate Recognition, Plate Type Recognition, Plate Color Recognition, Vehicle Type Classification, Vehicle Color Recognition, Vehicle Direction Detection, Speed Detection, Traffic Flow Detection
TRAILER DETAILS		SECURITY	
Axle rating	2150 lbs	Anti-theft	Dual locking compartment doors; Wheel lock immobilizes trailer
Mast Raise/Extension	12VDC Electric winch	CONNECTIVITY	
Mast height	25ft Mast	Ethernet	3G/4G cellular with WiFi
Wind Rating Speed	100 MPH	POWER SYSTEM	
BATTERY		Solar Panel	2 x 330W Monocrystal Silicon Solar Panel
No. of Battery	4 Sealed AGM x 150 Ah	Solar Controller	1 x Maximum Power Point Tracking Solar Controller
Capacity	600Ah	Low-voltage disconnect	Disengages power to equipment when battery voltage gets low; system automatically restarts when batteries are recharged; voltage and temperature settings are adjustable
Voltage	Low Voltage Battery Disconnect to prevent over-discharge of deep cycle batteries	Alerts	Low fuel, low oil, temperature
Charge controller	Precision 3-digit digital meter continuously displays battery voltage, and the load current	Operating Temperature	-30° to 60° C
AC Voltage	Normal operating mode 1 Amp 120 VAC, Charging mode 15 Amp 120VAC	PTZ CAMERAS (UP TO 5)	
Effective Pixels	Up to 3840x2160 (4k UHD)	Zoom Ratio	30x-36x



For PDF of PT-RD3000



For more Packetalk Trailers

GET IN TOUCH

CONTACT US

T (201) 355-3323
F (201) 603-6405
E sales@packetalk.net

PACKETALK.NET