

PT-RDDT6000
PT-RAPID DEPLOY DRONE TRAILER 6000

KEY FEATURES

• DRONE DETECTION
• DIESEL GENERATOR POWERED
• HD PTZ IP CAMERAS
• LARGE BATTERY BACKUP
• OPERATES IN EXTREME ENVIRONMENTS

• WIDE TRACK TRAILER FOR MAXIMUM STABILITY

(Typical Configuration)

LEARN MORE ABOUT THIS PRODUCT

Self-Contained

Rapid Deploy drone detection & surveillance systems that provide high definition live video of the deployment location

Remote Monitoring

Monitor critical areas, incident areas, and other problem locations whenever and wherever necessary in a compact, mobile, self-powered unit.

Pan-Tilt-Zoom (PTZ) Cameras

Configuration supports drone detection device & cameras including:

- 30x-36x Optical Zoom
- ALPR & OCR based Video Analytics
- Fixed Dome, 180° & 360° camera
- 360° Degrees of detail
- Up to 4k @ 90FPS video output

Management Software

Camera can be controlled automatically and precisely from anywhere using management software included with the system.

"Always On" Network

The system is shipped, preconfigured, and ready for deployment on leading broadband cellular networks.

On Board Self Healing

Autonomous operational continuity dashboard allows users to actively monitor and manage trailer vitals for all assets in a centralized location from desktop, phone, or tablet.



OUESTIONS? CONTACT US AT

201 355 3323 OR sales@packetalk.net







For PDF of PT-RDDT6000

For more Packetalk Trailers

PT-RDDT6000

BATTERY-POWERED WITH ON-BOARD DIESEL ENGINE CHARGER



CAMERA BOOM

Full drone detection & camera customization available with different PTZ functionality including ALPR, video analytics, people counting and thermal imagery.



BREAKERS & BATTERIES

Rapid deploy breakers protect internal components turning the trailer into an easy "Fire and Forget" asset.



ON BOARD SELF HEALING

Built in monitoring system collects data and information for display in our autonomous operational continuity vitals application.

SPECIFICATIONS

TOWER DIMENSIONS	
Width (Travel/Deployed)	79"/151"
Length	120"
Height (Travel/Deployed)	111"/300"
Weight (Dry/Operating)	2850 lbs
TRAILER DETAILS	
Axle rating	3500 lbs
Mast Raise/ Extension	12VDC Electric winch
Mast height	25ft Mast
Wind Rating Speed	125 MPH
BATTERY	
No. of Battery	2 sealed AGM x 250Ah
Capacity	500Ah
Voltage	Low Voltage Battery Disconnect to prevent over-discharge of deep cycle batteries
Charge controller	Precision 3-digit digital meter continuously displays battery voltage, and the load current
AC Voltage	Normal operating mode 1 Amp 120 VAC, Charging mode 15 Amp 120VAC

PTZ CAMERAS	
Effective Pixels	Up to 3840x2160 (4k UHD)
Zoom Ratio	30x-36x
Compression	MJPEG, H264, H265
Minimum Illumination	Color: 0.05 LUX@F1.6 B/W: 0.0 LUX@F1.6
Video Analytics	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed
Traffic Detection	License Plate Recognition, Plate Type Recognition, Plate Color Recognition, Vehicle Type Classification, Vehicle Color Recognition, Vehicle Direction Detection, Speed Detection, Traffic Flow Detection
SECURITY	
Anti-theft	Dual locking compartment doors; Wheel lock immobilizes trailer
DIESEL GENERATOR	
Engine	4 Stroke liquid-cooled 3 cylinder diesel engine
Fuel tank	56 Gallon Fuel Cell
Temperature control	Auto high/low temperature shutdown
Fuel consumption	.50 gph full load (1.89 Lph)
Vibration dampening	Rubber vibration dampers isolate engine/ generator from frame

GET IN TOUCH

CONTACT US

T (201) 355-3323

F (201) 603-6405

■ sales@packetalk.net

PACKETALK.NET