

CAMERA

PT-6500-HD BUBBLE



UNIQUE FEATURE

• **MOTORIZED ZOOM LENS**

Lens allows for precise remote configuration of focal length, Iris and focus to provide a clear image in all deployment scenarios.

SHARED KEY FEATURES

• **AI VIDEO ANALYTICS**

8 Intelligent OCR modes powered by AI engine which filters objects to focus on human and vehicle detection.

• **ULTRA LOW LIGHT**

Able to deliver high detailed color images even in 0.005LUX low light environments without any supplemental lighting.

• **UP TO 90 FPS**

Cameras catch images with no latency during high speed movement



PT-6500-HD1 BULLET

UNIQUE FEATURE

• **12X OPTICAL ZOOM**

Zoom onto distant subjects while still maintaining clarity delivering high quality video the entire zoom range.

QUESTIONS? CONTACT US AT
201 355 3323 OR sales@packetalk.net

PACKETALK.NET

SPECIFICATIONS		PT-6500-HD1 BULLET	PT-6500-HD BUBBLE
CAMERA	Image Sensor	1/2.8" Progressive Scan CMOS	
	Min. Illumination	Color: 0.005Lux@F1.6, B/W: 0Lux with IR on	Color: 0.005Lux@F1.4, B/W: 0Lux with IR on
	WDR	120dB Super WDR	
	Shutter Time	1/100000s~1s	
	IR Distance	Up to 180m	Up to 90m (7~22mm)
	Day/Night Mode	Day/Night/Auto/Customize/Schedule	
	S/N	>55dB	
LENS	Lens	5.3~64mm, 12X Optical Zoom	Motorized 2.7~13.5mm/ 3.0~10.5mm/7~22mm@F1.4
	Field of View	H61°~H5°/D69°~D5°/V36°~V2°	H115°~H34°/D135°~D39°/V62°~V19° (2.7~13.5mm) H93°~H33°/D107°~D38°/V52°~V18° (3.0~10.5m) H40°~H16°/D46°~D19°/V23°~V9° (7~22mm)
	Focus Control	Auto/Manual	
	Iris Control	Auto/Manual	
VIDEO	Max. Image Resolution	1920x1080	
	Video Compression	H.265*/H.265(HEVC)/H.264*/H.265/MJPEG	
	Image Setting	Brightness/Contrast/Saturation/Sharpness	
INTERFACE	Ethernet	1*RJ45 10M/100M Ethernet Port	
	Audio I/O	1/1	Built-in Microphone and 1 Audio Output interface
	Alarm I/O	1/1	
NETWORK	Network Storage	NAS (Support NFS, SMB/CIFS), ANR	
	Protocol	IPv4/IPv6, ARP, TCP, UDP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
AI	Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed	
SYSTEM	Storage	Support microSD/SDHC/SDXC Card Local Storage, up to 1 TB	
	Advanced Function	Heat Map, BLC, HLC, 2D DNR, 3D DNR, AWB, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur, Watermark	
	Event Trigger	Motion Detection, Network Disconnection, External Input, Audio Alarm, etc.	
	Event Action	FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP Notification, etc	
	System Compatibility	ONVIF Profile G & Q & S & T, API	
GENERAL	Working Temp.	-40°C~60°C	
	Working Humidity	0~90% (Non-condensing)	
	Power Supply	PoE (802.3at) / DC 12V±10%	
	Surge Protection	4KV	11W
	Weather Poof	Up to IP67-rated for Weather-resistant Performance	
	Housing	Vandal-proof IK10-rated Metal Housing	
	Weight	1447g	1100g
	Dimensions	320mmX134mmX126mm	Φ143mmX108.4mm

GET IN TOUCH

CONTACT US

T (201) 355-3323

F (201) 603-6405

E sales@packetalk.net

PACKETALK.NET