



LEARN MORE ABOUT THIS PRODUCT

Self-Contained

Temporary surveillance systems that provide high definition live video of the deployment location.

Remote Monitoring

Monitor critical areas, incident areas, and other problem locations whenever and wherever necessary in a compact, mobile, self-powered unit.

Management Software

Camera can be controlled automatically and precisely from anywhere using management software included with the system.

LED Boom

Up to 25Ft Mast equipped with 4 x 320 watt LED's. Lights are adjustable for 360 degree coverage.

Customized Alerts

Email, phone, and app alerts can be configured to notify users when action is needed for an asset Example Alerts:

- Service Due
- Battery Voltage Low
- Fuel Level Low
- Engine Run/Off

"Always On" Network

The system is shipped, preconfigured, and ready for deployment on leading broadband cellular networks.

On Board Self Healing

Autonomous operational continuity dashboard allows users to actively monitor and manage trailer vitals for all assets in a centralized location from desktop, phone, or tablet.



OUESTIONS? CONTACT US AT

201 355 3323 OR sales@packetalk.net



INNOVATIVE MULTI-TASK & SURVEILLANCE SOLUTIONS

PT-RD6000LT





LED

Mounted LED's adjustable to light up 360 degrees around the trailer and surrounding area



BREAKERS & BATTERIES

Rapid deploy breakers protect internal components turning the trailer into an easy "Fire and Forget" asset.



ON BOARD SELF HEALING

Built in monitoring system collects data and information for display in our autonomous operational continuity vitals application.

SPECIFICATIONS

AC Voltage

TOWER DIMENSIONS	
Width (Travel/Deployed)	79"/151"
Length	120"
Height (Travel/Deployed)	111"/300"
Weight (Dry/Operating)	2850 lbs
TRAILER DETAI	LS
Axle rating	3500 lbs
Mast Raise/ Extension	12VDC Electric winch
Mast height	25ft Mast
Wind Rating Speed	125 MPH
BATTERY	
No. of Battery	2 sealed AGM x 250Ah
Capacity	500Ah
Voltage	Low Voltage Battery Disconnect to prevent over-discharge of deep cycle batteries
Charge controller	Precision 3-digit digital meter continuously displays battery voltage, and the load current

Normal operating mode 1 Amp 120 VAC, Charging mode 15 Amp 120VAC

LIGHTED ELECTRONIC DIODES		
Lighting	4 x 320 watt LED Luminaries	
Controller	1 x SNMP Controller (Remote On/OFF for LEDs)	
SECURITY		
Anti-theft	Dual locking compartment doors; Wheel lock immobilizes trailer	
DIESEL GENERATOR		
Engine	4 Stroke liquid-cooled 3 cylinder diesel engine	
Fuel tank	56 Gallon Fuel Cell	
Temperature control	Auto high/low temperature shutdown	
Fuel consumption	.50 gph full load (1.89 Lph)	
Vibration dampening	Rubber vibration dampers isolate engine/ generator from frame	

GET IN TOUCH

CONTACT US

T (201) 355-3323

F (201) 603-6405

■ sales@packetalk.net

PACKETALK.NET