


TRAILER

# PT-RD6000-VMS

DIESEL-POWERED SURVEILLANCE TRAILER WITH VARIABLE MESSAGE BOARD

## KEY FEATURES

- DIESEL GENERATOR POWERED
- HD PTZ IP CAMERAS
- VARIABLE MESSAGE BOARD
- LARGE BATTERY BACKUP
- OPERATES IN EXTREME ENVIRONMENTS
- REAL-TIME MONITORING
- REMOTELY MONITORED AND CONTROLLED
- 24/7 UNATTENDED OPERATION
- WIDE TRACK TRAILER FOR MAXIMUM STABILITY



(Typical Configuration)

## LEARN MORE ABOUT THIS PRODUCT

### Self-Contained

Temporary surveillance systems that provide high definition live video of the deployment location.

### Remote Monitoring

Monitor critical areas, incident areas, and other problem locations whenever and wherever necessary in a compact, mobile, self-powered unit.

### Pan-Tilt-Zoom (PTZ) Cameras

Configuration supports up to three PTZ cameras supporting:

- 30x-36x Optical Zoom
- ALPR and OCR based Video Analytics
- Fixed Dome camera with up to 5x Zoom
- 360° Degrees of detail
- Up to 4k @ 90FPS video output

### ATS Variable Message Board

Cloud Management & Bluetooth support for variable message board and radar configuration.

### Management Software

Camera can be controlled automatically and precisely from anywhere using management software included with the system.

### “Always On” Network

The system is shipped, preconfigured, and ready for deployment on leading broadband cellular networks.

### On Board Self Healing

Autonomous operational continuity dashboard allows users to actively monitor and manage trailer vitals for all assets in a centralized location from desktop, phone, or tablet.

## CREATE A SMART CITY

POWERED BY PACKETALK

### ✓ Add a ALPR asset

Packetalk’s ALPR cameras have embedded license plate recognition, AI video analytics and up to 90FPS.



◀ PTZ-3160-HD36ALPR

### ✓ Add PTVAS

Packetalk Video Analytics System provides a multi-faceted situational awareness platform for all your surveillance needs.

### ✓ Deploy INAAP

Packetalk Interoperable National ALPR & Analysis Platform. Creates Interoperability across county and state lines for Plate recognition and vehicle exception reports. Equipped with API and third Party integration.

QUESTIONS? CONTACT US AT

201 355 3323 OR [sales@packetalk.net](mailto:sales@packetalk.net)

[PACKETALK.NET](http://PACKETALK.NET)

# PT-RD6000-VMS



### CAMERA BOOM

Full camera customization available with different PTZ functionality including ALPR, video analytics, people counting and thermal imagery.



### ATS VARIABLE MESSAGE BOARD

Variable Message Board attached to the trailer provides information to the public and surveillance in an all-in-one solution. The trailer can serve Public safety, OEM and other first responders needs.



### BREAKERS & BATTERIES

Rapid deploy breakers protect internal components turning the trailer into an easy "Fire and Forget" asset.



### ON BOARD SELF HEALING

Built in monitoring system collects data and information for display in our autonomous operational continuity vitals application.

## SPECIFICATIONS

### TOWER DIMENSIONS

Width (Travel/Deployed)	79"/151"
Length	120"
Height (Travel/Deployed)	111"/300"
Weight (Dry/Operating)	2850 lbs

### TRAILER DETAILS

Axle rating	3500 lbs
Mast Raise/Extension	12VDC Electric winch
Mast height	25ft Mast
Wind Rating Speed	125 MPH

### BATTERY

No. of Battery	2 sealed AGM x 250Ah
Capacity	500Ah
Voltage	Low Voltage Battery Disconnect to prevent over-discharge of deep cycle batteries
Charge controller	Precision 3-digit digital meter continuously displays battery voltage, and the load current
AC Voltage	Normal operating mode 1 Amp 120 VAC, Charging mode 15 Amp 120VAC

### VARIABLE MESSAGE BOARD

Open dimensions	1.63" x 28" x 60"
Folded dimensions	3.25" x 28" x 30"
Full matrix display	26 x 96 pixels, 0.6"x1" pitch
LED pixels	Amber 590nm, 30-degree viewing angle, 100,000 hrs, black background, MUTCD-compliant color, universal display modules Local and remote management and monitoring options
Weight	43 lbs

### PTZ CAMERAS (UP TO 3)

Effective Pixels	Up to 3840x2160 (4k UHD)
Zoom Ratio	30x-36x
Compression	MJPEG, H264, H265
Minimum Illumination	Color: 0.05 LUX@F1.6 B/W: 0.0 LUX@F1.6
Video Analytics	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed
Traffic Detection	License Plate Recognition, Plate Type Recognition, Plate Color Recognition, Vehicle Type Classification, Vehicle Color Recognition, Vehicle Direction Detection, Speed Detection, Traffic Flow Detection

### SECURITY

Anti-theft	Dual locking compartment doors; Wheel lock immobilizes trailer
------------	--

### DIESEL GENERATOR

Engine	4 Stroke liquid-cooled 3 cylinder diesel engine
Fuel tank	56 Gallon Fuel Cell
Temperature control	Auto high/low temperature shutdown
Fuel consumption	.50 gph full load (1.89 Lph)
Vibration dampening	Rubber vibration dampers isolate engine/ generator from frame

## GET IN TOUCH

### CONTACT US

**T** (201) 355-3323  
**F** (201) 603-6405  
**E** sales@packetalk.net

**PACKETALK.NET**