

INNOVATIVE MULTI-TASK & SURVEILLANCE SOLUTIONS

PT-RD4000

DIESEL-POWERED SURVEILLANCE TRAILER

KEY FEATURES

- DIESEL GENERATOR POWERED
- HD PTZ IP CAMERAS
- LARGE BATTERY BACKUP
- OPERATES IN EXTREME ENVIRONMENTS
- REAL-TIME MONITORING
- REMOTELY MONITORED AND CONTROLLED
- **24/7 UNATTENDED OPERATION**
- WIDE TRACK TRAILER FOR MAXIMUM STABILITY

(Typical Configuration)

LEARN MORE ABOUT THIS PRODUCT

Self-Contained

Temporary surveillance systems that provide high definition live video of the deployment location.

Remote Monitoring

Monitor critical areas, incident areas, and other problem locations whenever and wherever necessary in a compact, mobile, selfpowered unit.

Pan-Tilt-Zoom (PTZ) Cameras

Configuration supports up to three PTZ cameras supporting:

- 30x-36x Optical Zoom
- ALPR and OCR based Video Analytics
- Fixed Dome camera with up to 5x Zoom
- 360° Degrees of detail
- Up to 4k @ 90FPS video output

Management Software

Camera can be controlled automatically and precisely from anywhere using management software included with the system.

"Always On" Network

The system is shipped, preconfigured, and ready for deployment on leading broadband cellular networks.

On Board Self Healing

Autonomous operational continuity dashboard allows users to actively monitor and manage trailer vitals for all assets in a centralized location from desktop, phone, or tablet.

CREATE A SMART CITY

التوطئك بالمشا

OWERED BY PACKETALK

Add a ALPR asset

Packetalk's ALPR cameras have embedded license plate recognition, Al video analytics and up to 90FPS.



🗹 Add PTVAS

Packetalk Video Analytics System provides a multi-faceted situational awareness platform for all your surveillance needs.



Deploy INAAP

Packetalk Interoperable National ALPR & Analysis Platform. Creates Interoperability across county and state lines for Plate recognition and vehicle exception reports. Equipped with API and third Party integration.

QUESTIONS? CONTACT US AT 201 355 3323 OR sales@packetalk.net

© 2024, Packetalk. The Packetalk logo is a registered trademark of Packetalk. All other company names and products are trademarks or registered trademarks of their respective companies. All information provided is subject to change without notice.



PT-RD4000

BATTERY-POWERED WITH ON-BOARD DIESEL ENGINE CHARGER



CAMERA BOOM Full camera customization available with different PTZ functionality including ALPR, video analytics, people counting and thermal imagery.



BREAKERS & BATTERIES Rapid deploy breakers protect internal components turning the trailer into an easy "Fire and Forget" asset.



ON BOARD SELF HEALING Built in monitoring system collects data and information for display in our autonomous operational continuity vitals application.

SPECIFICATIONS

| TOWER DIMENSIONS | |
|-----------------------------|---|
| Width (Travel/Deployed) | 79"/151" |
| Length | 120″ |
| Height (Travel/Deployed) | 111"/300" |
| Weight (Dry/Operating) | 2235 lbs |
| TRAILER DETAILS | |
| Axle rating | 3500 lbs |
| Mast Raise/ Extension | 12VDC Electric winch |
| Mast height | 25ft Mast |
| Wind Rating Speed | 100 MPH |
| BATTERY | |
| No. of Battery | 2 sealed AGM x 250Ah |
| Capacity | 500Ah |
| Voltage | Low Voltage Battery Disconnect to prevent over-discharge of deep cycle batteries |
| Charge controller | Precision 3-digit digital meter continuously displays battery voltage, and the load current |
| AC Voltage | Normal operating mode 1 Amp 120 VAC, Charging mode 15 Amp 120VAC |

PTZ CAMERAS (UP TO 3) Up to 3840x2160 (4k UHD) **Effective Pixels** Zoom Ratio 30x-36x MJPEG, H264, H265 Compression Color: 0.05 LUX@F1.6 Minimum Illumination B/W: 0.0 LUX@F1.6 Region Entrance, Region Exiting, Advanced Motion Detection, Tamper **Video Analytics** Detection, Line Crossing, Loitering, Object Left, Object Removed License Plate Recognition, Plate Type Recognition, Plate Color Recognition, **Traffic Detection** Vehicle Type Classification, Vehicle Color Recognition, Vehicle Direction Detection, Speed Detection, Traffic Flow Detection SECURITY Dual locking compartment doors; Anti-theft Wheel lock immobilizes trailer DIESEL GENERATOR 4 Stroke liquid-cooled Engine 3 cylinder diesel engine Fuel tank 39 Gallon Fuel Cell Auto high/low temperature shutdown Temperature control .50 gph full load (1.89 Lph) **Fuel consumption** Vibration Rubber vibration dampers isolate dampening engine/ generator from frame



GET IN TOUCH

T (201) 355-3323 F (201) 603-6405 E sales@packetalk.net

PACKETALK.NET

© 2024, Packetalk. The Packetalk logo is a registered trademark of Packetalk. All other company names and products are trademarks or registered trademarks of their respective companies. All information provided is subject to change without notice.

INNOVATIVE MULTI-TASK & SURVEILLANCE SOLUTIONS